

Tow Boat Data Verification Sheet

(One Verification Sheet per Towboat)

Tournament Name - _____

Tournament Location _____

Chief Driver - _____ Rating - _____

Chief Driver Phone # _____

Boat Manufacturer/Model **Malibu Response Lxi Barefooter**

Vin # _____

Are the following secure and in place? Shaft; yes _____ no _____
Strut; yes _____ no _____
Rudder; yes _____ no _____
Prop; yes _____ no _____
Rope attachment Location(s) ; yes _____ no _____
Windshield, top or side mount mirror; yes _____ no _____

Are the following as tested?

	As tested	Boat at tournament
Engine:	383ci	_____ ci
Prop - size and pitch Also approved	Dia. 13" Pitch 12 5/8 13"X13"	Dia. _____ Pitch _____

Rear Judges seats placement - Trailing edge of judges seat no farther forward than even with Trailing edge of motor box cover.

Wake plate:

Dimensions Settings	Width 15 1/2" Length 10" Port/Starboard	Width _____ Length _____ Port/Starboard
---------------------	---	---

Turnbuckle turns:

Turns Down from neutral – 1 1/2 - 1 3/4 turns _____ / _____

Measured space (see NOTE) 3/32" to 1/8" _____

****NOTE**** Measured space is the distance between a straight edge and the space created by the bow of the plate (only the plate) when turn buckles are adjusted down from a neutral or flat position. The distance in the bow to the straight edge should not be greater than 3/32" to 1/8". This measurement is taken for each side of the plate.

Comments from Chief Driver
