Tow Boat Data Verification Sheet

(One Verification Sheet per Towboat)

Tournament Name _____ Date _____

Tournament Location _____

Chief Driver _____Rating _____

Chief Driver Phone # _____

Boat Manufacturer/Model __Sanger/Barefoot DXII

Vin # _____

Are the following secure and in place?

Shaft; yes _____ no _____
Strut; yes _____ no _____
Rudder; yes _____ no _____
Prop; yes _____ no _____
Rope attachment Location(s) ; yes _____ no _____
Windshield, top or side mount mirror; yes _____ no _____

Are the following as tested?

As tested

Engine: 5.7/330hp// 6.2/340hp // 6.2/380hp // 8.1/370hp // 8.1/420hp
Prop - 13x13 // 13x12.625 // 13x13 // 13x13 or 13.5x15 // 13x13 or 13.5x15.5

Circle engine and prop configuration of the boat at tournament.

Rear judges seat placement – trailing edge of judges seat no farther forward than even with Trailing edge of the motor box cover. Or bench seat flush with trailing edge of motor box.

Wake plate:

Dimensions	**Width 16'' Length 10''**	**Width_____Length_____**
Settings	**Port/Starboard**	**Port/Starboard**
Turnbuckle turns:		
Turns Down from neutral (approximate)	**__2__ /__2_____**	**_____/_____**
Measured space (see NOTE)	**__3/16 +/- 1/16 both sides**	**_____**

******NOTE**** Measured space is the largest space between a 24" long straight edge and the Wake plate. The 24" long straight edge shall be flushed to the trailing edge of the Wake plate and then held tight to the bottom of the hull along the edge of the Delta pad. This measurement is taken for each side of the plate.**

Comments from Chief Driver

_____

_____

_____